

Name	Standard	Symbol	Result
CE / DOP	EN 14041		CPR/AI/013
Usage Classification	EN ISO 10874		23, 34, 42
Manufacturing Standard	EN ISO 10582		
Size Dimensions - Planks	EN ISO 24342	Pcs / m2 12 / 2.75 Box / Pallet 60 / 165.20	1227mm x 187mm
Size Dimensions - Herringbone	EN ISO 24342	Pcs / m2 48 / 3.011 Box / Pallet 64 / 192.71	613.5 x 102.25
Total Thickness	EN ISO 24346		3.5 mm
Wear Layer Thickness	EN ISO 24340		0.7 mm
Weight	EN ISO 23997		4.5 kg/m ²
Abrasion Resistance	EN ISO 10582		Type 1
Wear resistance	EN 660-2		T
Residual Indentation	EN ISO 24343-1		≤ 0.1 mm (ave 0.05)
Dimensional Stability	EN ISO 23999		≤ 0.25% (avg 0.1)
Dimensional Stability / Curling	EN ISO 23999		≤ 2 mm
Slip Resistance	EN 13893		Class R10 (DS)
Slip Resistance	EN 16165 Annex B		PTV “Dry” 52. PTV “Wet” 44
Chemical Resistance	EN ISO 26987		Excellent
Colour Fastness to Light	EN ISO 105-B02		≥ 6
Flammability / Smoke Emissions	EN 13501-1		
Castor Chair Resistance (Type W)	EN ISO 4918		Pass
Furniture Leg Resistance	EN ISO 16581		No Crack, No Damage
Impact Sound Insulation	EN ISO 717-2		19 dB
Thermal Resistance	EN 12667		0.019(m2K)/W
Emissions	IAC Gold		Cert No. IACG-352-01-12-2024
Emissions	VOC Regulation		Very low emissions
Emissions	M1		Certified
Ortho-Phthalate Free			Yes – bio-based plasticisers
Surface Treatment			Heritage UV Coating
TVOC	EN 16000		A+
Formaldehyde Group	EN 14041:2004/ AC:2006		E1
Environmental product declaration	EN 15804:2012+ A2:2019		Certified report that transparently shows a product's full environmental impact from manufacture to disposal.
IAQ Certification			FloorScore®: Pass — certified as low-emitting flooring meeting all CA 01350 VOC emission requirements.